

# C310

## Exceed All Expectations



ASK Proxima's new C310 is a testament to your company's ingenuity and success. This performance-oriented meeting room projector allows you to present with power featuring 3000 lumens, and ultimate connectivity afforded by the onboard M1-DA port which allows expansion to HDMI, DVI, VGA and even USB functions. With such a bright image, this projector is perfect for those meetings when the lights must stay on or the window shades open. All of this power comes with great adjustability as well, such as digital keystone correction, RGB color-adjustment, an impressive 1000:1 contrast ratio and multiple installation options.

### Advanced Technology

The C310 was engineered to be your ally in the office – always performing for you and brilliant. We've eliminated excess operating noise while increasing the color-depth, ensuring each person in the meeting room enjoys the show while hearing your every word. DLP® technology from Texas Instruments™ enables a lifetime of image clarity without those annoying LCD panel filters to worry about. With the C310's crisp, clear XGA resolution, fine details will shine through like never before.

### For the Final Details

Day after day and meeting upon meeting, the C310 will continue to satisfy your needs and impress your audience. Utilizing onboard micro-adjust zoom and focus controls each user can maximize image size and clarity. Reliability and ease of maintenance are a big advancement for the C310 – we've built this projector to be even more durable and long-lasting with the great benefit of the ASX Proxima warranty service.

### A Shared Experience.

Whether you're unveiling your company's latest product concept or reviewing detailed contracts, the C310 will make every meeting a collaborative experience. The C310 is extremely easy to set-up with the included color-coded cables, and a breeze to move from room-to-room, so you can be influential anywhere you choose.



Flexible controls and M1-DA connectivity allows expansion to HDMI, DVI, VGA and USB - so you can display pictures, video, spreadsheets or slideshows in perfect clarity from virtually any source.



Multiple inputs and flexible installation options make this the best projector for your conference room.

**ASK Proxima TECHNICAL SPECIFICATIONS\***

Native Resolution	XGA 1024 x 768
Display Technology	DLP® by Texas Instruments™: 0.7" XGA DDR DMD
Input Sources	2 Computer (DVI-M1-DA and VESA); 2 Video (S-Video 4-pin mini DIN and Composite RCA); 1 Audio (stereo RCA); 1 Serial Interface (RJ45)
Output Sources	Monitor Out (VESA); Stereo Audio (3.5 mm)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, Macintosh®
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i)
Brightness	3000 max ANSI lumens
Contrast Ratio	1000:1
Number of Colors	16.7 million
Projection Distance	4.92'-33' (1.5-10 m)
Brightness Uniformity	-30%
H-Synch Range	15.625-85 kHz
V-Synch Range	48-85 Hz
Dot Clock	13.5 MHz-140 MHz
Digital Keystone Correction	+30/-25 degrees vertical correction; video/data
Projection Lens	Zoom lens with manual focus and manual zoom adjustment
Zoom Ratio	1.2:1
Throw Ratio (distance/image width)	1.83:1-2.27:1
Minimum Projection Distance	4.92' (1.5 m)
Image Offset Ratio %	115%
Aspect Ratio	4:3 (native) and 16:9
Image Size (diagonal)	32" (82.5 cm) to greater than 264" (670 cm)
Projection Methods	Front, ceiling, rear, rear ceiling
Audio	3.0 Watt
Control	Projector keypad, IR remote control, USB via M1-DA-D/A, RS232 serial via RJ45
Lamp	200W SHP / 2000 hour user replaceable
Product Dimensions	2.93 in H x 10.36 in W x 8.57 in L (7.44 cm H x 26.31 cm W x 21.77 cm L)
Product Weight	5.0 lbs (2.27 kg)
Product Color	Black with Silver
Shipping Weight	10 lbs (4.5 kg)
Shipping Dimensions	8" H x 20" L x 15" W (20.32 cm H x 50.86 cm W x 38.10 cm L)
Power Consumption	260W
Power Supply	90-265 VAC at 50/60 Hz
Operating Temperature	10-35°C at sea level to 7500' (2286 m), 50-95°F
Ships with	Computer cable (with tie wrap), power cable (with tie wrap), carry case, lens cap, remote control, user guide, detailed reference guide, CD
Menu Languages	English, German, French, Italian, Spanish, Swedish, Portuguese, Russian, Chinese (simplified)
Audible Noise	35dBa in Low Power Mode
Approvals	UL and c-UL (US/Canada), FCC-A (US/Canada), CE (CE member countries), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), C-Tick (Australia)

\* All specifications subject to change

\*\* Some resolutions may require Component/Vesa adapter

\*\*\* Resolution support may be product specific

\*\*\*\* Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

**SHIPS STANDARD WITH:**

- Lens cap
- Wireless Navigator Remote Control (including batteries)
- Computer cable
- RCA Video and Audio cable
- Power cord
- SCART adapter (EMEA Only)
- Projector System CD includes: multi-language User Guide, Quick Start Card, URL/service information/accessories after market
- User Guide (printed version)
- Quick Start Card (printed version)

**OPTIONAL ACCESSORIES**

HW-PRESENTER	Presenter Remote
HW-PRESENTER-RF	Presenter RF Remote
HW-CONDUCTOR+	Conductor Plus Remote
SP-DVI-D	Digital Computer Cable

**SERIOUS COMMITMENT**

ASK Proxima's dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. ASK Proxima projectors come with a standard two-year limited factory warranty, including parts and labor, a 90-day or one-year accessory warranty, and a six-month lamp replacement warranty. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit: [www.infocus.com/service/service\\_offerings](http://www.infocus.com/service/service_offerings)



# ASK Proxima

[www.askproxima.com](http://www.askproxima.com)

**InFocus Corporate Headquarters:** 27500 SW Parkway Avenue  
Wilsonville, Oregon 97070-9215, USA • Phone: (1) 503-685-8888  
(1) 800-294-6400 • Fax: (1) 503-685-8887

**In Europe:** InFocus International BV • Louis Armstrongweg 110 • 1311 RL Almere  
The Netherlands • Fax: (31) 36 5392999  
Freephone: 008000 4636287 (008000 INFOCUS)

**In Asia:** 19 Tanglin Road • 7<sup>th</sup> Floor  
Singapore 247909 • Telephone: (65) 6513-9600 • Fax: (65) 6238-0510